WorkCentre 7232
shown with the Two Tray option.

WorkCentre 7242
shown with High-Capacity Tandem Tray and Office Finisher options.

	WorkCentre® 7232	WorkCentre® 7242
OUTPUT SPEED – Printing and Copying		
Black and White	Up to 32 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF, Up to 16 ppm 8.5 x 14 in. (216 x 356 mm), Up to 16 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 40 ppm 8.5 x 11 in. (A4/210 x 297 mm) LEF, Up to 20 ppm 8.5 x 14 in. (216 x 356 mm) Up to 20 ppm 11 x 17 in. (A3/297 x 420 mm)
Color	Up to 10 ppm 8.5 x 11 in. (A4/210 x 297 mm) Up to 5 ppm 8.5 x 14 in. (216 x 356 mm) Up to 5 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 10 ppm 8.5 x 11 in. (A4/210 x 297 mm) Up to 5 ppm 8.5 x 14 in. (216 x 356 mm) Up to 5 ppm 11 x 17 in. (A3/297 x 420 mm)
FIRST-IMAGE-OUT TIME		
Black and White	As fast as 15 seconds	
Color	As fast as 24 seconds	

	Print Specifications
SYSTEM	
Memory	1.2 GB
System Disk	40 GB

Print Specifications

NETWORK PRINTING – Network Controller

Processor	667 MHz
Printer Languages (auto sensing/switching)	Adobe® Postscript® 3™ (optional) TIFF PCL® 5c PDF 1.5 PCL® 6 HP-GL2™ XPS®

NETWORK PRINTING – Resolution

600 x 600 x 4 dpi (achieves 1200dpi with resolution enhancement)

NETWORK PRINTING – Printing Features

Features	Print Calibration Secure print Delay print (specific time) Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermark Fit to new paper size Transparency separators Banner sheet enable/disable Output tray selection Image quality (High Speed, High Quality) Draft mode Store and recall driver settings Reduce/enlarge Mirror image Margins Email Print Bi-Directional
Driver Settings	• Application specific saved settings – uses the registry of the application to print per preferences set on client PC. Works at server for applications hosted on a server. Driver only feature. Can not be cascaded to users from a server. • Driver Pre-Configuration – enables drivers to be configured to an administrator-defined standard before being pushed out. Driver only feature. • Context Based Restrictions — allows administrator to setup users to restrict printing on several levels including applications. Supported via the device and the driver.

Continued

Print Specifications

PRINT PROTOCOLS AND NETWORKS

Physical

100 Base-TX/10 BaseT
USB 2.0 printer port
Wireless Ethernet (IEEE 802.11b) via third-party adapters
Bluetooth via third-party adapters

Operating Systems

Microsoft® Windows® 2000, XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Vista 32-bit, Windows Vista 64-bit
Mac OS® 10.3 and above (requires optional PostScript 3 Kit)
AIX 5lv5.3
HP UX 11.0, 11i v2
Solaris 8, 9, 10
Linux® FedoraCore 1, 5
RedHat Enterprise Linux 4
SUSE 10.x

Network Protocols

TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, IPv6
Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway), TCP/IP
AppleTalk®: EtherTalk®
Microsoft Windows Networking over IP and NetBEUI
(All protocols not in use can be disabled)

Administrative Protocols

DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL

Fonts

Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts
PCL: 84 scalable fonts, line printer bitmap font

Print Drivers (Vista XPS mini driver available)

Environment	*PCL5c and PCL 6*	*PostScript (requires optional Kit)*
Windows 2000/XP Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bidirectional with user-selectable interface (standard** and enhanced*)	Bidirectional with user-selectable interface (standard** and enhanced*)
Macintosh® System OS 10.3.0 and above	N/A	Enhanced PPD file
UNIX	Bidirectional with user-selectable interface (standard** and enhanced*)	Bidirectional with user-selectable interface (standard** and enhanced*)

Print Submission Tools

- Command prompt LPR/UNIX tool for print submission
- Xerox TIFF submission tool supports TIFF and PDF: Supported in Windows 2000/XP/Vista/Windows Server 2005
- Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
- Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print

**Enhanced: Xerox custom graphical user interface.*
***Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)*

	Print Specifications
DEVICE MANAGEMENT	
Management Support	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
Xerox CentreWare Web	• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
IP Filter	Allows administrator to control print access to device via IP address.
Xerox CentreWare® for Unicenter TNG®	• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View • Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk
Xerox CentreWare® for Tivoli® Netware®	• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView • Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet • Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)
Xerox CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	• Provides for the identification of Xerox N-Series printers and WorkCentre multifunction devices in the general discovery performed by HP OpenView • Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons • Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView

Continued

Print Specifications

DEVICE MANAGEMENT (Continued)

Xerox Device Types for SAP R/3 Environment	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): —Simplex or duplex printing —Finishing—single or dual stapling —Tray pull location from any tray —Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via Type House 800-445-3668	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller —Tray status/contents —Consumables status
Xerox Barcode Pro PS (optional) Purchase via Type House 800-445-3668	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

SMart eSolutions

Meter Assistant	Device Direct or via proxy
Supplies Assistant	Device Direct or via proxy

CENTREWARE® INTERNET SERVICES – Integrated Device Web Page

Device Status	Web server embedded on SMart Network Controller™ —Tray status/contents —Consumables status
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Windows® XP, 2000: Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x

Continued

	Scan Specifications
SCANNING (Optional)	
Capability	Color Scanning, Greyscale, Black and White (Auto Color Detection)
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Input Speed	Scan at 50 ipm monochrome/45 ipm color (216 x 279 mm/A4 long edge feed)
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (monochrome), 8 bit (grayscale), 24 bit (color)
Maximum Scan Area	11.7 x 17in./297 x 432 mm
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows 2000/Windows Server 2003/Vista) LDAP
Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP
File Formats	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF with JPEG, G3 MH, MRC, G4 MMR, MRC (optional), or JPEG compression JPEG PDF XPS Format Text Searchable PDF (optional)
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard Only for Network Scan through templates
Scan Features	Mixed size originals Bound originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression

Continued

Scan Specifications

SCANNING (Optional) (Continued)

Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Professional and SE editions) Scan to Windows XP client SMB or FTP Scan to Mailbox Scan to Home Scan to PC Scan to Searchable PDF/XPS
Scan to PC Desktop SE	— A desktop and server-based offering that provides document imaging, archiving, editing and organization tools — ScanSoft PaperPort – image viewing and file management software — ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software — Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
Scan to PC Desktop Pro	— A desktop and server based offering that provides document imaging, archiving, editing and organization tools — ScanSoft PaperPort Pro – image viewing and file management software — ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software — Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability.

EMAIL (Included with Scan to Email Kit or Network Scan Kit)

Capability	Color scanning, Auto Color, Grayscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching “From” field auto-populated from LDAP
Network Protocol	SMTP, MIME, LDAP, LDAP with SSL
Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2000/Windows 2003 Server) LDAP Domino
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)

SCAN TO MAILBOX (Included with the Scan to Email Kit)

Capability	Color, Auto Color, Black and White
Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scanned images that are stored in the mailbox can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB server.

Fax Specifications

NETWORK FAX SERVER INTEGRATION (Optional-requires one of the scan options)

Fax Send Features	One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
Fax Vendors	Multiple vendors, certified by the Xerox Business Partners Program For details, visit **www.xerox.com**

FAX (Optional) - Standard with One or Three Line Fax Option

	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
Speed/Compression	MH/G3, MMR/G4, JBig Super G3
Fax Send Features	Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan PSTN Fax (VOIP and DSL not supported) Internet Fax LAN Fax Phone number entry via keyboard or address book Secure Fax via FCODE
Fax Receive Features	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention FCODE Secure Fax Fax forward to mailbox based on incoming fax number
Fax Forward to Email	When enabled with the scan and fax kit, faxes can be received into a mailbox. Using Job Flow Sheets, images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax.

Continued

Fax Specifications

FAX (Optional) - Standard with One or Three Line Option (Continued)	
Fax Reports	Activity report Dial directory Transmission confirmation Pending fax Mailbox
Fax Receive Mailboxes	Up to 200 password-protected mailboxes
Auto Dialing	Auto redial, Batch send
Single Line option	Total of 200 speed dials (single-line option) Up to 200 dial groups with up to 200 recipients per group (single line option)
Three Line option	1,000 speed dials (three line option) Up to 400 dial groups with up to 400 recipients per group (three line option)
INTERNET FAX (Optional) - Standard with One or Three Line Fax Option	
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in color and black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	11.7 x 17 in./297 x 432 mm
Address Directory Access	Downloaded address list (comma-separated file format)
File Formats	TIFF-FX Profiles S, F with G3 MH, or G4 MMR
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome), 8 bit (greyscale)
Network Protocols	SMTP POP3
Compliance	ITU-T T.37 compliant

	Copy Specifications
COPYING	
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto color selection Poster mode Watermark Annotation Bates Stamp Area Designation Full color Single/Dual color Copy calibration

Continued

Copy Specifications

COPYING (Continued)

Special Features	Booklet creation Multi-up—2, 4 or 8 up Transparency dividers Negative image Mirror image Covers insertion (front only, front and back; blank or printed) Build Job (enables special programming for different pages in one document—can be used for inserts, different paper sources,and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Book copying Sample job Mixed-size originals Stapling (single/dual) ID Card Copy
Foreign Device Interface	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service

Device Specifications

PAPER HANDLING - Duplex Automatic Document Feeder

Capacity	75 sheets (based on 20 lb bond/80 gsm paper)
Speed	50 images per minute black and white/45 images per minute color (Letter/A4 long edge feed (LEF))
Sizes	4.9 x 4.5 in (125 x 115 mm) to 11.7 x 17 in. (297 x 432 mm) and standard sizes of 5.5 x 8.5 in. to 11 x 17 in. (A5 to A3)
Weights	16 to 32 lb bond/38 to 128 gsm

Device Specifications

PAPER HANDLING - Bypass Tray	
Capacity*	100 sheets
Sizes	3.5 x 3.9 in. (A6/89 x 98.4 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb bond to 80 lb Cover/55 to 216 gsm
Types	Same as front-loading trays plus label stock and envelopes
PAPER HANDLING - Front-Loading Paper Tray (Standard)	
Capacity*	520 sheets
Sizes	User adjustable from 5.5 x 7.2 in. (A5/139.7 x 182 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	17 lb bond to 80 lb Cover/55 to 216 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
PAPER HANDLING - Input Tray Options - Three Tray Option (Tray One plus Two Tray Module)	
Tray 2 - Tray 3	520 sheets
Sizes	User adjustable from 5.5 x 7.2 in. (A5/139.7 x 182 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	17 lb bond to 80 lb Cover/55 to 216 gsm

Continued

**Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.*

Device Specifications

PAPER HANDLING - Input Tray Options - Two Tray Option (Tray One plus Two Tray Module) (Continued)

Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
Total Capacity*	1,660 sheets (Includes Tray 1, Tray 2, Tray 3 and Bypass Tray)

PAPER HANDLING - Input Tray Options - High-Capacity Tandem Tray Option (Tray One plus Tandem Tray)

Tray 1	520 sheets
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Tray 2 ***Tray 3***	900 sheets 1,200 sheets
Sizes	8.5 x 11 in., B5, A4
Weights	17 lb bond to 80 lb Cover/64 to 216 gsm

Continued

**Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.*

Device Specifications

PAPER HANDLING - Input Tray Options - High-Capacity Tandem Tray Option (Continued)	
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Lightweight Heavyweight Extra Heavyweight Transparency Heavyweight Gloss Labels Gloss Extra Heavyweight Gloss Punched Letterhead Pre-printed Envelopes
Total Capacity*	2,720 sheets (Includes Tray 1, Tray 2, Tray 3 and Bypass Tray)
PAPER HANDLING - High-Capacity Feeder (HCF) (Compatible with two tray module and High Capacity Tandem Tray)	
Capacity	2,000 sheets of 20 lb bond (75 gsm)
Sizes	8.5 x 11 in. LEF (A4/210 x 297 mm), 7.25 x 10.5 LEF (184 x 266.7 mm)
Weights	17 lb bond to 80 lb cover (64 to 216 gsm)
Total Capacity*	4,720 sheets with High Capacity Tandem Tray—3,660 sheets with two tray module
OUTPUT - Integrated Office Finisher Option	
Stacking Tray	500 sheets of 20 lb bond (80 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb bond (80 gsm) 11 x 17 in./A3
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	18 lb bond to 80 lb cover/60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum less than 90 gsm or (2) 220 gsm covers) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

Continued

**Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.*

	Device Specifications
OUTPUT - Office Finisher Option	
Stacking Tray	1,000 sheets of 24 lb bond (90 gsm)
Sizes	8 x 10 in./B5 to 11 x 17 in./A3
Weights	18 lb bond to 80 lb cover/60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
SECURITY	
Capability	Secure Print, Password Protected PDF, timed auto delete secure print, NDS Authentication over IP, Encrypted Scan to Email (with Scan option), LDAP/Kerberos/SMB, IPv6, 802.1x, IPSec, IP Filtering
Optional Data Security Kit Capability	Encrypted Disk and Audit Log. Hard disk overwrite immediate or on demand. Secure Web Page via SSL.
ACCOUNTING	
Accounting with Third-Party Server Applications (optional)	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax
Auditron	Controls and tracks black and color copy, print, fax and scan usage, supports up to 1,000 user accounts Color access via Active Directory Network Accounting
Internal Auditron	Controls and tracks black and color copy and print usage, supports up to 1,000 user accounts Note: Option to upload/download account and usage data via direct connection using Windows-based software. Limits user to black-only copy and print
Accounting Control	Xerox Standard Accounting Job based accounting Third-party integration Supports Foreign Device Interface Active directory user profile—Controls color copy and print usage

Continued

	Device Specifications
ACCOUNTING - Xerox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 750 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.

	WorkCentre® 7232	WorkCentre® 7242
MONTHLY DUTY CYCLE		
	100,000	125,000

BASIC CONFIGURATIONS*
Network Multifunction System with network controller—Copy and Print capability standard Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations

Continued

**Features, configurations and options may vary by location.*

Device Specifications

ACCESSORIES

Office Finisher
Integrated Office Finisher
One-line fax option
Three-line fax option
Foreign Device Interface
Network Accounting Enablement
Scan to Email with Scan to Mailbox
Scan Performance Kit
Network Scanning With Email
PostScript Kit
Fax Server Kit
Data Security Kit
Scan to PC Desktop Client Software (Professional or SE edition)
External High Capacity Feeder
HIgh Capacity Tandem Tray Option
Two tray module
Mobile Stand

ELECTRICAL REQUIREMENTS

220–240 V Nominal, 50/60 Hz, 10A
100-127 Vac, 50/60 Hz, 12A

POWER CONSUMPTION

Running	< 311 watts
Standby	< 118 watts
Low-Power Mode	< 89 watts
Sleep Mode	< 6.3 watts
Warm Up	45 seconds (maximum)
Low-Power Recovery	30 seconds (maximum)

**Features, configurations and options may vary by location.*

Device Specifications

POWER CONSUMPTION

Required Temperature Range	50° to 82° F (10° to 28° C)
Required Relative Humidity	15% to 85%
Noise Emission	32 dB(A) standby 56 dB(A) running
Heat Emission	1060 BTU/Hr running 402 BTU/Hr standby

DIMENSIONS AND WEIGHT	*width*	*depth*	*height*	*weight*
Base Unit	25.2 in./640 mm	25.7 in./654 mm	43.8 in./1,112 mm	187 lbs/85 kg
Base Unit with Integrated Office Finisher	25.2 in./640 mm	25.7 in./654 mm	43.8 in./1,112 mm	212 lbs/96.3 kg
Base Unit with Office Finisher	60.5 in./1,537 mm	26.3 in./668 mm	43.8 in./1,112 mm	253 lbs/115 kg

XEROX EXTENSIBLE INTERFACE PLATFORM™ (EIP)

Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customized user interfaces, and card-based authentication solutions supporting a personalized user experience.

The WorkCentre 7232/7242 supports Xerox Secure Access Unified ID System™ and Xerox SMARTsend™ at launch. More EIP applications will be supported post launch.

CERTIFICATIONS

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)
89/336/EEC (Europe)
UL Listed (UL60950-1, First Edition)
CB Certified (IEC 60950-1/EN 60950-1)
73/23/EEC (Europe)
Novell Tested and Approved
Windows Hardware Quality Labs

Device Specifications

SUPPLIES	*Description*	*Order Number*
Toner Cartridges	Black	006R01318
	Cyan	006R01269
	Magenta	006R01268
	Yellow	006R01267
Staple Refills	For Office Finisher	008R12915
	For Integrated Finisher	008R12941
SMART KITS		
	Smart Kit™ Drum Cartridge	013R00636
	Smart Kit™ Waste Bottle	008R13021
	Smart Kit™ Fuser Assembly (220 V)	008R13045
	Smart Kit™ Fuser Assembly (110 V)	008R13044
	Smart Kit™ IBT Belt Cleaner unit	001R00593

© 2007 Xerox Corporation. All rights reserved. XEROX®, WorkCentre®, CentreWare® and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product information and/or specifications are subject to change without notice. 9/07 610P729370A W42SS-01UB